


# INTERNATIONAL SWAT CONFERENCE

10-12 January 2018, IIT Madras, Chennai, India

SWAT-MODFLOW, AN OPTIMIZATION MODEL FOR CONJUNCTIVE USE OF SURFACE AND GROUNDWATER OF NAGARJUNA SAGAR CATCHMENT

B. Hima Bindu

Dept. of Civil Engineering  
IIT Hyderabad



Dr. T. Shashidhar


Dept. of Civil Engineering  
IIT Hyderabad

DEPARTMENT OF CIVIL ENGINEERING  
INDIAN INSTITUTE OF TECHNOLOGY HYDERABAD

Date: 10-Jan-18




## OVERVIEW



- Problem identification



- Objectives



- Study area






- Data collection



- Model setup




- Results and conclusion



**Source:** Indian Meteorological Department and Directorate Of Economics And Statistics


# Raising and falling trends of Ground water levels



- Average water level trend
- pre monsoon water level trend
- Post monsoon water level trend




- No significant fall of water table noticed in Guntur district when compared to Khammam
- About 83% of the wells are showing general rising trend of 0.0015 to 0.7684 m/year and the rest 17% of the wells are showing falling trend varying from 0.0101 to 0.4833m/year in Guntur District



# Study area

Khammam(Telangana)



Guntur(Andhra Pradesh)



# Objectives

- To develop and test the feasibility of the integrated modelling framework for surface and groundwater hydrological models (SWAT-MODFLOW)



# Data collection

## DEM

- [srtm.csi.cgiar.org](http://srtm.csi.cgiar.org)

## Soil and LULC

- [www.waterbase.org](http://www.waterbase.org)

## Climate data

- <https://globalweather.tamu.edu/#pubs>

SWAT

MODFLOW

Source: *Central Ground water department, 2013*


Specific storage

Specific yield


Aquifer thickness

Hydraulic conductivity

# CONJUNCTIVE USE



**HOW**



SWAT-MODFLOW is an integrated hydrological model that couples SWAT land surface processes with spatially-explicit groundwater flow processes



It helps to develop optimum conjunctive use model







# SWAT model setup


## KHAMMAM



# SWAT model setup



# SWAT- RESULTS



PRECIPITATION = 1226.4 MM

SURFACE RUNOFF Q = 298.82 MM

GROUNDWATER (SHAL AQ) Q = 240.5 MM

GROUNDWATER (DEEP AQ) Q = 14.71 MM

REVAP (SHAL AQ => SOIL/PLANTS) = 39.36 MM

DEEP AQ RECHARGE = 14.74 MM

TOTAL AQ RECHARGE = 294.83 MM

TOTAL WATER YLD = 564.85 MM

PERCOLATION OUT OF SOIL = 295.08 MM




ET = 621.3 MM

PET = 1967.8 MM



# SWAT model setup

## GUNTUR



# SWAT- RESULTS

## Rainfall-Runoff analysis of Guntur

PRECIPITATION = 1474.4 MM

SURFACE RUNOFF Q = 720.84 MM

GROUNDWATER (SHAL AQ) Q = 152.13 MM

GROUNDWATER (DEEP AQ) Q = 9.59 MM

REVAP (SHAL AQ => SOIL/PLANTS) = 32.51 MM

DEEP AQ RECHARGE = 9.63 MM


TOTAL AQ RECHARGE = 192.65 MM

TOTAL WATER YLD = 885.96 MM


PERCOLATION OUT OF SOIL = 192.70 MM

ET = 557.3 MM

PET = 1930.6MM




# Hydrological modelling of Madhira Sub basin (Khammam)



# Calibration parameters- SWATCUP-Madhira

Sl.No	Parameter_Name	Fitted_Value	Min_value	Max_value
1	R__CN2.mgt	-0.084562	-0.100000	-0.010000
2	V__GW_DELAY.gw	175.730774	30.0	180.000000
3	A__GWQMN.gw	20.300001	80.000000	50.000000
4	A__REVAPMN.gw	42.884624	350.000000	100.000000
5	V__GW_REVAP.gw	0.163692	0.100000	0.180000
6	R__SOL_K(..).sol	0.145000	0.300000	0.200000
7	R__SOL_AWC(..).sol	0.338615	0.200000	0.400000
8	V__ESCO.bsn	0.733346	0.700000	0.850000
9	V__EPCO.bsn	0.572385	0.400000	0.700000


# Calibration and validation graphs of Madhira



	Calibration		Validation	
Objective Function	R <sup>2</sup>	NSE	R <sup>2</sup>	NSE
	0.67	0.63	0.7	0.43

Calibration period: 1985 – 2006


Validation period : 2007 -- 2013




SWAT-CUP has been used for model calibration and validation




# SWAT-MODFLOW of Madhira




# SWAT-MODFLOW of Madhira




# Madhira DEM







# Hydrological modelling of Pondugala sub basin







# SWAT-MODFLOW







# SWAT-MODFLOW



# SWAT-MODFLOW



# SWAT-MODFLOW





# Conclusion

- SWAT-MODFLOW setup has been carried out for Pondugala(Guntur) and Madhira (Khammam) watershed.
- The calibration and validation results of Madhira shows good relation between observed and simulated.
- It is observed that surface runoff of Guntur district shows high values when compared to Khammam District.
- The ground water levels of Khammam and Guntur was estimated using SWAT-MODFLOW.
- Evaluation of management strategies has to be carried out with the help of Linear programming model.

Thank you

# Calibration parameters- SWATCUP-Pondugala

Sl.No	Parameter_Name	Fitted_Value	Min_value	Max_value
1	:R__CN2.mgt	-0.179200	-0.190000	-0.150000
2	V__GW_REVAP.gw	0.065167	0.050000	0.180000
3	R__SOL_AWC(..).sol	0.350000	0.500000	0.500000
4	R__CN2.mgt	-0.059567	-0.120000	-0.050000
5	V__ESCO.bsn	0.124667	0.000000	0.200000
6	R__CN2.mgt	-0.126500	-0.150000	-0.120000
7	V__ALPHA_BF.gw	0.304133	0.250000	0.330000
8	V__EPCO.bsn	0.421333	0.300000	0.700000
9	A__GWQMN.gw	260.333344	200.000000	300.000000
10	V__GW_DELAY.gw	34.950001	30.000000	75.000000
11	A__REVAPMN.gw	88.266670	40.000000	120.000000
12	12:R__RES_K.res	-0.400333	-0.800000	-0.300000

